SUB-TILLER ECO

3.00 m with hydraulic auto-release system, 4 tines, Square tube roller and hydr. depth control.

3.00 m. with hydraulic auto-release system and 4 tines.

- Tine height under the frame 820 mm.
- Max. working depth 600 mm.
- Good clearance with a frame height of 820 mm.
- Strong frame construction, 180x180x8 mm sectional tubes.
- 3 stone protection types: Shear bolt, Quick-Push or Hydraulic automatic.
- Infinitely variable tine spacing, depending on the models and number of tines.

- For machines with roller:
- Hydr. depth control for Square Tube Roller and V-Profile Roller. (Requires one double-acting oil outlet)

MACHINES

				Without Roller	Square Tube Roller Ø550 mm	V-Profile Roller Ø600 mm
Work Width, m	Stone Protection	No. of Tines	Row Spacing, cm	Item Number	Item Number	Item Number
2.50	Quick-Push	2	180	64541-01	64542-01	64543-01
2.50	Quick-Push	3	90	64541-02	64542-02	64543-02
2.50	Hydr. auto.	2	180	64541-06	64542-06	64543-06
2.50	Hydr. auto.	3	90	64541-07	64542-07	64543-07
3.00	Quick-Push	2	200	64541-11	64542-11	64543-11
3.00	Quick-Push	3	100	64541-12	64542-12	64543-12
3.00	Quick-Push	4	75	64541-13	64542-13	64543-13
3.00	Hydr. auto.	2	200	64541-16	64542-16	64543-16
3.00	Hydr. auto.	3	100	64541-17	64542-17	64543-17
3.00	Hydr. auto.	4	75	64541-18	64542-18	64543-18
3.50	Quick-Push	5	70	64541-20	64542-20	64543-20
3.50	Hydr. auto.	5	70	64541-26	64542-26	64543-26

							
						Without Roller	Square Tube Roller Ø550 mm	V-Profile Roller Ø600 mm
Work Width, m	Stone Protection	No. of Tines	Row Spacing, cm	Power Req., HP	Max HP	Weight, kg		
2.50	Quick-Push	2	180	60-100	250	500	860	1,375
2.50	Quick-Push	3	90	90-120	250	580	940	1,445
2.50	Hydr. auto.	2	180	60-100	250	540	900	1,405
2.50	Hydr. auto.	3	90	90-120	250	630	990	1,495
3.00	Quick-Push	2	200	60-100	250	520	930	1,550
3.00	Quick-Push	3	100	90-120	250	600	1,010	1,630
3.00	Quick-Push	4	75	110-160	250	680	1,090	1,710
3.00	Hydr. auto.	2	200	60-100	250	580	990	1,610
3.00	Hydr. auto.	3	100	90-120	250	690	1,100	1,720
3.00	Hydr. auto.	4	75	110-160	250	810	1,220	1,840
3.50	Quick-Push	5	70	130-200	250	780	1,260	1,980
3.50	Hydr. auto.	5	70	130-200	250	900	1,380	2,100

**All models require 1 double-acting oil outlet*

IMPORTANT:

If a change of stated row spacing is wanted, please inform when placing an order. Max. total tine spacing from the two outer tines is always 55 cm less than the work width.

STANDARD EQUIPMENT

- Hydr. depth control incl. depth scale for Square Tube Roller and V-Profile Roller.
- Three-point linkage with cat. 3 pins and cat. 2 distance.
- Supporting leg on machines without roller.
- For Quick-push stone protection: 8 steps per bolt.
- Scraper between the V-Profile rings.
- Points with 200 mm wing shares, mounted on 25 mm wide tine.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
Points with 120 mm wing shares (Price reduction per tine)	-	645000043A
Points 120 mm with hard metal plate (Additional price per tine)	-	645000043TA
Points with 350 mm wing shares (Additional price per tine)	-	645000063A
Points 200 mm with hard metal plate (Additional price per tine)	-	645000044TA
Cat.II pins for three-point mounting	-	64509-08
Check valve (pilot-controlled) for hydr. depth control	-	64543-85
Set of reflective warning boards (2 pieces)	-	67055-74
LED lights complete w/wire and socket	3	64509-01
Tine for retro mounting complete, Quick-Push stone protection	85	645000112
Tine for retro mounting complete, Hydr. stone protection	121	645000114
Tine reinforcement, hard metal 60x25x15 mm incl. factory fitting on new tine. Recommended when tilling > 350 mm. (Additional price per tine)	-	645000085