TRIPLE-TILLER (THREE-POINT MOUNTED)

- Optimal cultivating with only 25 cm row spacing.
- 3 rows of harrow sections with good clearance with 85 cm frame height, 75 cm tine spacing and 70 cm bar spacing.
- 3 tine options
  - Spring tine double-twisted. Work depth: 0 - 20 cm:
    - 35 x 35 mm for 2.50 - 3.50 m models
    - 40 x 40 mm for 4.00 - 6.00 m models
  - Shear bolt - preloaded for 2550 kg. Work depth: 0 - 30 cm
  - Automatic w/double spring /auto reset preloaded for 455 kg. Work depth: 0 - 30 cm
- Eradicator discs, standard equipment, w/centre spindle adjustment, stone protected by rubber suspension.
- Hydr. depth adjustment –w/depth stop by means of distance clips.

MACHINES

THREE-POINT MOUNTED RIGID 1-SECTION MODELS WITHOUT HYDRAULIC FOLDING

Work Width, m	Roller Type		Stone Protection	No. of Tines	Power Req., HP	Lifting Req., kg	Transport Width, m	Weight, kg	Item Number
3.00	Square tube roller Ø550 mm	1*	Spring tine	12	100-200	4,070	3.00	1,850	4503022
3.00	Square tube roller Ø550 mm	1*	Shear bolt	12	100-200	4,070	3.00	1,850	4503024
3.00	Square tube roller Ø550 mm	1*	Automatic	12	100-200	4,070	3.00	1,850	4503020
3.00	Wave roller Ø600 mm	1*	Spring tine	12	100-200	-	3.00	-	4503072
3.00	Wave roller Ø600 mm	1*	Shear bolt	12	100-200	-	3.00	-	4503074
3.00	Wave roller Ø600 mm	1*	Automatic	12	100-200	-	3.00	-	4503070
3.00	U-Profile roller Ø600 mm	1*	Spring tine	12	100-200	5,000	3.00	2,100	4503082
3.00	U-Profile roller Ø600 mm	1*	Shear bolt	12	100-200	5,000	3.00	2,100	4503084
3.00	U-Profile roller Ø600 mm	1*	Automatic	12	100-200	5,000	3.00	2,100	4503080
3.00	V-Profile roller Ø600 mm	1*	Spring tine	12	100-200	5,430	3.00	2,470	4503062
3.00	V-Profile roller Ø600 mm	1*	Shear bolt	12	100-200	5,430	3.00	2,470	4503064
3.00	V-Profile roller Ø600 mm	1*	Automatic	12	100-200	5,430	3.00	2,470	4503060
3.50	Square tube roller Ø550 mm	1*	Spring tine	14	120-240	4,690	3.50	2,135	4503522
3.50	Square tube roller Ø550 mm	1*	Shear bolt	14	120-240	4,690	3.50	2,135	4503524
3.50	Square tube roller Ø550 mm	1*	Automatic	14	120-240	4,690	3.50	2,135	4503520
3.50	Wave roller Ø600 mm	1*	Spring tine	14	120-240	-	3.50	-	4503572
3.50	Wave roller Ø600 mm	1*	Shear bolt	14	120-240	-	3.50	-	4503574
3.50	Wave roller Ø600 mm	1*	Automatic	14	120-240	-	3.50	-	4503570
3.50	U-Profile roller Ø600 mm	1*	Spring tine	14	120-240	5,620	3.50	2,540	4503582
3.50	U-Profile roller Ø600 mm	1*	Shear bolt	14	120-240	5,620	3.50	2,540	4503584
3.50	U-Profile roller Ø600 mm	1*	Automatic	14	120-240	5,620	3.50	2,540	4503580
3.50	V-Profile roller Ø600 mm	1*	Spring tine	14	120-240	6,290	3.50	2,860	4503562
3.50	V-Profile roller Ø600 mm	1*	Shear bolt	14	120-240	6,290	3.50	2,860	4503564
3.50	V-Profile roller Ø600 mm	1*	Automatic	14	120-240	6,290	3.50	2,860	4503560
4.00	Square tube roller Ø550 mm	1*	Spring tine	16	140-250	5,290	4.00	2,420	4534022
4.00	Square tube roller Ø550 mm	1*	Shear bolt	16	140-250	5,290	4.00	2,420	4534024
4.00	Square tube roller Ø550 mm	1*	Automatic	16	140-250	5,290	4.00	2,420	4534020
4.00	Wave roller Ø600 mm	1*	Spring tine	16	140-250	-	4.00	-	4534072
4.00	Wave roller Ø600 mm	1*	Shear bolt	16	140-250	-	4.00	-	4534074
4.00	Wave roller Ø600 mm	1*	Automatic	16	140-250	-	4.00	-	4534070
4.00	U-Profile roller Ø600 mm	1*	Spring tine	16	140-250	6,570	4.00	3,010	4534082
4.00	U-Profile roller Ø600 mm	1*	Shear bolt	16	140-250	6,570	4.00	3,010	4534084
4.00	U-Profile roller Ø600 mm	1*	Automatic	16	140-250	6,570	4.00	3,010	4534080
4.00	V-Profile roller Ø600 mm	1*	Spring tine	16	140-250	7,185	4.00	3,300	4534062
4.00	V-Profile roller Ø600 mm	1*	Shear bolt	16	140-250	7,185	4.00	3,300	4534064
4.00	V-Profile roller Ø600 mm	1*	Automatic	16	140-250	7,185	4.00	3,300	4534060

*1*Requires 1 double-acting oil outlet.*

MACHINES (CONTINUED)

THREE-POINT MOUNTED 2-SECTION MODELS WITH HYDRAULIC FOLDING								
Work Width, m	Roller Type	Stone Protection	No. of Tines	Power Req., HP	Lifting Req., kg	Transport Width, m	Weight, kg	Item Number
4.00	Square tube roller Ø550 mm [1*]	Spring tine	16	140-250	6,470	2.48	3,240	4504022
4.00	Square tube roller Ø550 mm [1*]	Shear bolt	16	140-250	6,470	2.48	3,240	4504024
4.00	Square tube roller Ø550 mm [1*]	Automatic	16	140-250	6,470	2.48	3,240	4504020
4.00	Wave roller Ø600 mm [1*]	Spring tine	16	140-250	-	2.48	-	4504072
4.00	Wave roller Ø600 mm [1*]	Shear bolt	16	140-250	-	2.48	-	4504074
4.00	Wave roller Ø600 mm [1*]	Automatic	16	140-250	-	2.48	-	4504070
4.00	U-Profile roller Ø600 mm [1*]	Spring tine	16	140-250	8,100	2.48	3,760	4504082
4.00	U-Profile roller Ø600 mm [1*]	Shear bolt	16	140-250	8,100	2.48	3,760	4504084
4.00	U-Profile roller Ø600 mm [1*]	Automatic	16	140-250	8,100	2.48	3,760	4504080
4.00	V-Profile roller Ø600 mm [1*]	Spring tine	16	140-250	8,290	2.48	4,070	4504062
4.00	V-Profile roller Ø600 mm [1*]	Shear bolt	16	140-250	8,290	2.48	4,070	4504064
4.00	V-Profile roller Ø600 mm [1*]	Automatic	16	140-250	8,290	2.48	4,070	4504060

[1]Requires 2 double-acting oil outlets.*

STANDARD EQUIPMENT

- 75 x 12 mm reversible and height adjustable concave wearing point (double curved).
- Ø410 mm scalloped eradicator discs with centre spindle adjustment, stone protected by rubber suspension.
- Ø550 mm Square tube roller, Ø600 mm Wave Roller, Ø600 mm U-Profile or V-Profile roller.
- Scraper between the rings, on Wave roller, Single V and U-Profile roller.
- Automatic transport locking devices, operated hydr. together w/the folding function.
- All models have hydr. depth adjustment of the roller with the possibility of fixed stop via the distance clips.
- Three-point linkage with cat. 3 pins and cat. 2 distance

TRIPLE-TILLER (TRAILED)

- Optimal cultivating with only 25 cm row spacing.
- 3 rows of harrow sections with good clearance with 85 cm frame height, 75 cm tine spacing and 70 cm bar spacing.
- 3 tine options:
  - Spring tine double-twisted. Work depth: 0 - 20 cm:
    - 35 x 35 mm for 2.50 - 3.50 m models
    - 40 x 40 mm for 4.00 - 6.00 m models
  - Shear bolt - preloaded for 2550 kg. Work depth: 0 - 30 cm
  - Automatic w/double spring /auto reset preloaded for 455 kg. Work depth: 0 - 30 cm
- Eradicator discs, standard equipment, w/centre spindle adjustment, stone protected by rubber suspension.
- Hydr. depth adjustment –w/depth stop by means of distance clips.

MACHINES

TRAILED RIGID 1-SECTION MODELS WITHOUT HYDRAULIC FOLDING

Work Width, m	Roller Type		Stone Protection	No. of Tines	Power Req., HP	Transport Width, m	Weight, kg	Item Number
3.00	Square tube roller Ø550 mm	[1*]	Spring tine	12	100-200	3.00	2,430	4513022
3.00	Square tube roller Ø550 mm	[1*]	Shear bolt	12	100-200	3.00	2,430	4513024
3.00	Square tube roller Ø550 mm	[1*]	Automatic	12	100-200	3.00	2,430	4513020
3.00	Wave roller Ø600 mm	[1*]	Spring tine	12	100-200	3.00	-	4513072
3.00	Wave roller Ø600 mm	[1*]	Shear bolt	12	100-200	3.00	-	4513074
3.00	Wave roller Ø600 mm	[1*]	Automatic	12	100-200	3.00	-	4513070
3.00	U-Profile roller Ø600 mm	[1*]	Spring tine	12	100-200	3.00	2,700	4513082
3.00	U-Profile roller Ø600 mm	[1*]	Shear bolt	12	100-200	3.00	2,700	4513084
3.00	U-Profile roller Ø600 mm	[1*]	Automatic	12	100-200	3.00	2,700	4513080
3.00	V-Profile roller Ø600 mm	[1*]	Spring tine	12	100-200	3.00	3,050	4513062
3.00	V-Profile roller Ø600 mm	[1*]	Shear bolt	12	100-200	3.00	3,050	4513064
3.00	V-Profile roller Ø600 mm	[1*]	Automatic	12	100-200	3.00	3,050	4513060
3.50	Square tube roller Ø550 mm	[1*]	Spring tine	14	120-240	3.50	2,715	4513522
3.50	Square tube roller Ø550 mm	[1*]	Shear bolt	14	120-240	3.50	2,715	4513524
3.50	Square tube roller Ø550 mm	[1*]	Automatic	14	120-240	3.50	2,715	4513520
3.50	Wave roller Ø600 mm	[1*]	Spring tine	14	120-240	3.50	-	4513572
3.50	Wave roller Ø600 mm	[1*]	Shear bolt	14	120-240	3.50	-	4513574
3.50	Wave roller Ø600 mm	[1*]	Automatic	14	120-240	3.50	-	4513570
3.50	U-Profile roller Ø600 mm	[1*]	Spring tine	14	120-240	3.50	3,100	4513582
3.50	U-Profile roller Ø600 mm	[1*]	Shear bolt	14	120-240	3.50	3,100	4513584
3.50	U-Profile roller Ø600 mm	[1*]	Automatic	14	120-240	3.50	3,100	4513580
3.50	V-Profile roller Ø600 mm	[1*]	Spring tine	14	120-240	3.50	3,440	4513562
3.50	V-Profile roller Ø600 mm	[1*]	Shear bolt	14	120-240	3.50	3,440	4513564
3.50	V-Profile roller Ø600 mm	[1*]	Automatic	14	120-240	3.50	3,440	4513560
4.00	Square tube roller Ø550 mm	[1*]	Spring tine	16	140-250	4.00	3,090	4544022
4.00	Square tube roller Ø550 mm	[1*]	Shear bolt	16	140-250	4.00	3,090	4544024
4.00	Square tube roller Ø550 mm	[1*]	Automatic	16	140-250	4.00	3,090	4544020
4.00	Wave roller Ø600 mm	[1*]	Spring tine	16	140-250	4.00	-	4544072
4.00	Wave roller Ø600 mm	[1*]	Shear bolt	16	140-250	4.00	-	4544074
4.00	Wave roller Ø600 mm	[1*]	Automatic	16	140-250	4.00	-	4544070
4.00	U-Profile roller Ø600 mm	[1*]	Spring tine	16	140-250	4.00	3,615	4544082
4.00	U-Profile roller Ø600 mm	[1*]	Shear bolt	16	140-250	4.00	3,615	4544084
4.00	U-Profile roller Ø600 mm	[1*]	Automatic	16	140-250	4.00	3,615	4544080
4.00	V-Profile roller Ø600 mm	[1*]	Spring tine	16	140-250	4.00	3,900	4544062
4.00	V-Profile roller Ø600 mm	[1*]	Shear bolt	16	140-250	4.00	3,900	4544064
4.00	V-Profile roller Ø600 mm	[1*]	Automatic	16	140-250	4.00	3,900	4544060

[1]Requires 2 double-acting oil outlets.*

MACHINES (CONTINUED)

TRAILED 2-SECTION MODELS WITH HYDRAULIC FOLDING

Work Width, m	Roller Type	Stone Protection	No. of Tines	Power Req., HP	Lifting Req., kg	Transport Width, m	Weight, kg	Item Number
4.00	Square tube roller Ø550 mm [1*]	Spring tine	16	140-250	6,470	2.48	3,240	4514022
4.00	Square tube roller Ø550 mm [1*]	Shear bolt	16	140-250	6,470	2.48	3,240	4514024
4.00	Square tube roller Ø550 mm [1*]	Automatic	16	140-250	6,470	2.48	3,240	4514020
4.00	U-Profile roller Ø600 mm [1*]	Spring tine	16	140-250	8,100	2.48	3,760	4514082
4.00	U-Profile roller Ø600 mm [1*]	Shear bolt	16	140-250	8,100	2.48	3,760	4514084
4.00	U-Profile roller Ø600 mm [1*]	Automatic	16	140-250	8,100	2.48	3,760	4514080
4.00	V-Profile roller Ø600 mm [1*]	Spring tine	16	140-250	8,290	2.48	4,070	4514062
4.00	V-Profile roller Ø600 mm [1*]	Shear bolt	16	140-250	8,290	2.48	4,070	4514064
4.00	V-Profile roller Ø600 mm [1*]	Automatic	16	140-250	8,290	2.48	4,070	4514060
5.00	Square tube roller Ø550 mm [1*]	Spring tine	16	140-250	6,470	2.48	4,550	4515022
5.00	Square tube roller Ø550 mm [1*]	Shear bolt	16	140-250	6,470	2.48	4,550	4515024
5.00	Square tube roller Ø550 mm [1*]	Automatic	16	140-250	6,470	2.48	4,550	4515020
5.00	U-Profile roller Ø600 mm [1*]	Spring tine	16	140-250	8,100	2.48	5,230	4515082
5.00	U-Profile roller Ø600 mm [1*]	Shear bolt	16	140-250	8,100	2.48	5,230	4515084
5.00	U-Profile roller Ø600 mm [1*]	Automatic	16	140-250	8,100	2.48	5,230	4515080
5.00	V-Profile roller Ø600 mm [1*]	Spring tine	16	140-250	8,290	2.48	5,540	4515062
5.00	V-Profile roller Ø600 mm [1*]	Shear bolt	16	140-250	8,290	2.48	5,540	4515064
5.00	V-Profile roller Ø600 mm [1*]	Automatic	16	140-250	8,290	2.48	5,540	4515060

[1*]*Requires 3 double-acting oil outlets.*

STANDARD EQUIPMENT

- 75 x 12 mm reversible and height adjustable concave wearing point (double curved).
- Ø410 mm scalloped eradicator discs with centre spindle adjustment, stone protected by rubber suspension.
- Ø550 mm Square tube roller, Ø600 mm Wave Roller, Ø600 mm U-Profile or V-Profile roller.
- Scraper between the rings, on Wave roller, Single V and U-Profile roller.
- Automatic transport locking devices, operated hydr. together w/the folding function.
- Wheels :
  - 3.00 and 3.50 m 1-section: 11.5/80x 15.3 – 14 PLY
  - 4.00 m 1-section: 4.00 m and 5.00 m 2-section: 400/60 x 15.5 – 16 PLY
- Pivotal towing eye, secured by bolts, item no.. 630757017
- Three-point linkage with cat. 3 pins and cat. 2 distance

EXTRA EQUIPMENT - THREE-POINT MOUNTED / TRAILED

Work Width, m	Description	Weight, kg	Item Number
3.00 - 5.00	Set of reflective warning boards (2 pieces)	-	67055-74
3.00 - 4.00	LED lights complete with wire and socket mounted on three-point mounted 1-section models	3	4519510
4.00	LED lights with wire and socket,mounted on three-point mounted 2-section models	3	4519515
3.00 - 5.00	Narrow wear point, 50x25 mm – Same price as for standard point	-	4509310
-	Edge disc set - hydraulic folding (Price per set)	33	4519451
-	Edge disc set - rigid (Price per set)	33	4519452
3.00 - 3.50	Trail kit for rigid models, 11.5/80x15.3	580	4519701
4.00	Trail kit for rigid model, 400/60x15.5	590	4519702
4.00	Trail kit for models with hydraulic folding, 400/60x15.5	650	4519705
-	Support /depth wheels mounted in front (only trailed models)	275	4519750

QUICK CHANGE KIT - INCL. ONE SET OF CHISEL POINTS 75 MM WIDE AND ONE SET OF 260 MM WIDE WING SHARES.

Work Width, m	Description	Weight, kg	Item Number
3.00	"Quick change kit" with twisted mould board, **factory-mounted** (Additional price)	20	4509030
3.50	"Quick change kit" with twisted mould board, **factory-mounted** (Additional price)	23	4509035
4.00	"Quick change kit" with twisted mould board, **factory-mounted** (Additional price)	26	4509040
5.00	"Quick change kit" with twisted mould board, **factory-mounted** (Additional price)	33	4509050
3.00 - 5.00	"Quick change kit" with twisted mould board. (Left) **retro mounting** (Price per tine)	-	4509019
3.00 - 5.00	"Quick change kit" with twisted mould board. (Right) **retro mounting** (Price per tine)	-	4509020
3.00	"Quick change kit" with straight mould board, **factory-mounted** (Additional price)	23	4509230
3.50	"Quick change kit" with straight mould board, **factory-mounted** (Additional price)	27	4509235
4.00	"Quick change kit" with straight mould board, **factory-mounted** (Additional price)	30	4509240
5.00	"Quick change kit" with straight mould board, **factory-mounted** (Additional price)	38	4509250
3.00 - 5.00	"Quick change kit" with straight mould board. **retro mounting** (Price per tine)	-	4509220

MOUNTING SET FOR MULTI-SEEDER INCL. MOUNTING ON NEW TRIPLE-TILLER - MAX. 300 KG LOAD IN FINE SEED HOPPER. PRICES AND INFO ON MULTI-SEEDER

Work Width, m	Type	Description	Item Number - 8 Outlets
3.00 - 4.00	Rigid	For three-point mounted and trailed models	4509930
4.00 - 5.00	Hydraulic	For trailed models - only for AC and EC-models	4509940
4.00	Hydraulic	For three-point mounted models	4509435